



JAC 2.5T ELECTRIC FORKLIFT PERFORMANCE PARAMETERS



Model		型 号		Unit	CPD25
Load Capacity		额定起升重量		Kg	2500
Max loading capacity at highest		最大载重升至最高		Kg	1700
Load Center		载荷中心距		mm	500
Mast Lifting height		门架起升高度		mm	4500
Mast Free Lift		门架自由起升高度		mm	1125
Mast lifting Speed (With Load)		门架最大起升速度（满载）		mm/s	280
Mast tilt (Front/Rear)		门架倾角 前/后			6°/ 6°
Driving Speed(Full load)		行驶速度（满载）		km/h	13
Gradeability (With Load)		爬坡力(满载)		%	15
Turning Radius		最小转弯半径		mm	2060
Ground clearance		最小离地间隙		mm	100
Form Size	Overall length(without fork)	外 形 尺 寸	全长(无货叉)	mm	2331
	Overall width		全宽	mm	1160
	Height of overhead guard		全高(至护顶架)	mm	2025
	Height of mast, extended		全高(门架全伸出)	mm	5435
Wheelbase		轴 距		mm	1520
Tread	Front	前轮距		mm	960
	Rear	后轮距		mm	960
Standard fork		标准货叉（长x宽x厚）		mm	40x120x1070
Service Weight		自 重		kg	4580
Battery	capacity	电池组	容量	V/Ah	48/630
	size:l/w/h		箱体:长宽高	mm	1168x836x825
	weight		自重	kg	700
Motor	traveling	电机	行走	kw	11
	lifting		起升	kw	8.6

