



JAC 3T ELECTRIC FORKLIFT PERFORMANCE PARAMETERS



Model		型 号		Unit	CPD30
Load Capacity		额定起升重量		Kg	3000
Max loading capacity at highest		最大载重升至最高		Kg	2700
Load Center		载荷中心距		mm	500
Mast Lifting height		门架起升高度		mm	4500
Mast Free Lift		门架自由起升高度		mm	908
Mast lifting Speed (With Load)		门架最大起升速度 (满载)		mm/s	240
Mast tilt (Front/Rear)		门架倾角 前/后			6°/ 6°
Driving Speed(Full load)		行驶速度 (满载)		km/h	13
Gradeability (With Load)		爬坡力 (满载)		%	15
Turning Radius		最小转弯半径		mm	2440
Ground clearance		最小离地间隙		mm	120
Form Size	Overall length(without fork)	外 形 尺 寸	全长(无货叉)	mm	2597
	Overall width		全宽	mm	1304
	Height of overhead guard		全高(至护顶架)	mm	2155
	Height of mast, extended		全高(门架全伸出)	mm	5775
Wheelbase		轴 距		mm	1719
Tread	Front	前轮距		mm	1060
	Rear	后轮距		mm	980
Standard fork		标准货叉 (长x宽x厚)		mm	1070x125x45
Service Weight		自 重		kg	5570
Battery	capacity	电池组	容量	V/Ah	80/500
	size:l/w/h		箱体:长宽高	mm	1168x836x825
	weight		自重	kg	1200
Motor	traveling	电机	行走	kw	16
	lifting		起升	kw	13

