



JAC 3T GASOLINE & LPG FORKLIFT PERFORMANCE PARAMETERS



Model		型 号		Unit	CPQYD30
Load Capacity		额定起升重量		Kg	3000
Max loading capacityat highest		最大载重升至最高		Kg	2600
Load Center		载荷中心距		mm	500
Mast Lifting height		门架起升高度		mm	4500
Mast Free Lift		门架自由起升高度		mm	870
Mast lifting Speed (With Load)		门架最大起升速度（满载）		mm/s	460
Mast tilt (Front/Rear)		门架倾角 前/后			6°/6°
Driving Speed		行驶速度		km/h	19
Gradeability (With Load)		爬坡力(满载)		%	20
Turning Radius		最小转弯半径		mm	2500
Ground clearance		最小离地间隙		mm	160
Form Size	Overall length(without forks)	外 形 尺 寸	全长(无货叉)	mm	2740
	Overall width		全宽	mm	1230
	Height of overhead guard		全高(至护顶架)	mm	2100
	Height of mast, extended		全高(门架全伸出)	mm	5730
Wheelbase		轴 距		mm	1700
Tread	Front	前轮距		mm	1000
	Rear	后轮距		mm	970
Overhang (front)		前悬距		mm	476
Fork		标准货叉 （长x宽x厚）		mm	1220×125×45
Service Weight		自 重		kg	4750
Engine	Model	发动机	型 号		Nissan GCTK25
	Rated Output		额定功率	KW	37.4
	Rated power speed		额定功率时转速	rpm	2300

