



JAC 4T ELECTRIC FORKLIFT PERFORMANCE PARAMETERS



Model		型 号		Unit	CPD40
Load Capacity		额定起升重量		Kg	4000
Max loading capacity at highest		最大载重升至最高		Kg	2600
Load Center		载荷中心距		mm	500
Mast Lifting height		门架起升高度		mm	5500
Mast Free Lift		门架自由起升高度		mm	1285
Mast lifting Speed (With Load)		门架最大起升速度 (满载)		mm/s	200
Mast tilt (Front/Rear)		门架倾角 前/后			3°/ 6°
Driving Speed(Full load)		行驶速度 (满载)		km/h	13
Gradeability (With Load)		爬坡力 (满载)		%	15
Turning Radius		最小转弯半径		mm	2650
Ground clearance		最小离地间隙		mm	130
Form Size	Overall length(without fork)	外 形 尺 寸	全长(无货叉)	mm	2712
	Overall width		全宽	mm	1440
	Height of overhead guard		全高(至护顶架)	mm	2560
	Height of mast, extended		全高(门架全伸出)	mm	6800
Wheelbase		轴 距		mm	1830
Tread	Front	前轮距		mm	1184
	Rear	后轮距		mm	1025
Standard fork		标准货叉 (长x宽x厚)		mm	1220x125x50
Service Weight		自 重		kg	6830
Battery	capacity	电池组	容量	V/Ah	80/600
	size:l/w/h		箱体:长宽高	mm	1210x685x835
	weight		自重	kg	1600
Motor	traveling	电机	行走	kw	18
	lifting		起升	kw	25

